


Study 28

Reach 1A Spawning Area Bed Mobility

**Public Draft
2013 Monitoring and Analysis Plan**

**SAN JOAQUIN RIVER
RESTORATION PROGRAM**



1 **28.0 Reach 1A Spawning Area Bed**

2 **Mobility**

3 **28.1 Statement of Need**

4 The Problem Statement for Healthy Fry Production expresses the need to understand the
5 limiting factors to healthy fry production, which include egg survival and redd
6 superimposition (SJRRP, 2009). Egg survival is dependent on intragravel flow delivery
7 of DO, which is influenced by the fine sediment content within the gravel interstices.
8 Redd superimposition is dependent on availability of suitable spawning gravels relative
9 to the number of spawning pairs. The suitability of spawning gravels is not only based on
10 grain size composition but also the looseness of the bed material such that it allows ease
11 of redd construction. Therefore, understanding the condition of the stream bed (i.e.,
12 texture, amount of sand and silt, and the degree of bed reinforcement) in areas that are
13 otherwise expected to be suitable for spawning (i.e., have sufficient flow velocity and
14 depth during spawning and incubation periods) is pertinent to the success of the
15 restoration effort.

16 Bed surface coarsening (a.k.a. armoring) is often exacerbated by the installation of dams
17 that reduce sediment supply to downstream reaches. An armored bed effectively traps
18 finer sediment beneath and between the stable surface particles. These fine sediments
19 inhibit intragravel flow and therefore reduce DO delivery as well as metabolic waste
20 removal. By entraining coarsened surface particles, fine sediments (sand, silt, and clay)
21 trapped within the bed framework can be flushed (Reisser, et al., 1989). Theoretically,
22 there are two beneficial outcomes of this process. The first is that by reducing the
23 concentration of fine sediment the stream bed is better ventilated thereby increasing
24 oxygen delivery to and waste removal from incubating embryos (Kondolf, 2000). The
25 second is that the armored surface is often in a locked pavement-like state, and by
26 breaking it apart, a looser structure is then created that facilitates redd construction
27 (Wilcock et al., 1996). Loose, mobile gravels allow spawning salmon to construct a redd
28 of sufficient depth so as to protect their eggs from predation and physical stream
29 processes. A reinforced bed condition will limit, redd construction to looser areas. If such
30 areas are limited relative to available spawners redd superimposition will be encouraged.
31 Therefore, where the stream bed is reinforced to such a degree as to inhibit redd
32 construction spawning areas quantified solely by flow conditions and surficial grain size
33 composition, the amount of spawning area will be overestimated. For both these reasons,
34 a stream bed surface that is able to be mobilized is a condition necessary to maintain
35 suitable salmon spawning and incubation habitat.

1 **28.2 Background**

2 Several studies have concluded that bed material mobilization required to maintain
3 salmon spawning habitat and create in-channel and channel-margin habitat in Reach 1A
4 generally requires flows in the range of 12,000 to 16,000 cfs (MEI, 2002; JSA and MEI,
5 2002; McBain and Trush, 2002; Stillwater Sciences, 2003), well above the maximum
6 Restoration releases called for in the Settlement. Hydraulic and sediment transport
7 analysis by MEI (2002), however, showed that some local reworking of the bed should
8 occur at flows in the 3,000 to 8,000 cfs range. This analysis specifically indicated that
9 bed mobilization would occur at flows of less than 3,500 cfs at riffle clusters 38 (RM
10 260.6), 40 (RM 261.4), 43 (RM 264.7), 46 (RM 266.6), and 47 (RM 266.7). Grain size
11 analysis of the San Joaquin River's bed near riffle crests indicates an armored condition
12 (DWR, 2009). Since the expectation is that the majority of the riffles exhibit a nonmobile
13 condition in anticipated Restoration release scenarios, spawnable areas are predicted to be
14 reinforced and have reduced intragravel flow. Therefore, it is necessary to quantify the
15 extent of those areas that are mobile and thereby maintained by more frequent flow
16 levels. In addition, measurements will be collected to allow for a reliable prediction of the
17 discharge necessary to disrupt the reinforced bed surfaces and flush the trapped fine
18 sediment.

19 **28.3 Anticipated Outcomes**


20 Results of this study will provide information to accomplish the following:

- 21 • Characterize bed material relative to requirements for incubating embryos
22 proximal to anticipated spawning areas (i.e., riffles, runs, and pool tail-outs) at
23 finer resolution than is currently available.
- 24 • Measure the frictional resistance of the existing bed surface.
- 25 • Calculate the threshold shear stress for incipient motion specific to critical
26 areas.
- 27 • Calibrate and validate a sediment transport and flow model that can be
28 extended throughout upper Reach 1A.
- 29 • Use the calculated threshold shear stress to predict the rare high-magnitude
30 flow events necessary to entrain the reinforced channel beds and maintain
31 suitable habitat.
- 32 • Develop the requisite understanding of the relationship between stream
33 discharge and stream habitat maintenance.
- 34 • Refine the estimated quantity of available spawning gravels based on: (1) area
35 maintained by anticipated pulse flow levels, (2) bed material characteristics,
36 (3) flow depth, and (4) velocity during spawning and incubation relevant flow

1 levels. Provide information for alternatives to maintain a sufficient quantity of
 2 productive spawning gravels.

3 28.4 Methods

4 At least two monitoring sites were selected at locations where analytical modeling
 5 suggests bed mobilization will occur at flows of less than 3,500 cfs (MEI, 2008). To
 6 assess bed mobility, several measurements will be collected such that their combination
 7 can be used to develop a predictive model of bed material mobility. These tasks will
 8 include measuring the force required to mobilize surface gravel particles, characterizing
 9 particle size, deploying and monitoring radio frequency identification tagged (RFID)
 10 gravel and cobble tracers, repeated topographic surveys, monitoring scour chains,
 11 surveying flow hydraulics, and developing a calibrated and tested flow and sediment
 12 transport model (Figure 28-1).



13
 14 **Figure 28-1.**
 15 **Flow Diagram for Predicting Bed Mobility and Flushing Flow Maintained Habitat**

16 28.4.1 Force Gaging

17 Force measurements and particle characterization surveys will be conducted at the onset
 18 of the study. Force gaging will be performed using submergible, spring-resisting, push-
 19 pull force measuring devices. Force gaging will be performed in areas delineated within
 20 approximately 20 feet of monitoring cross sections. Particles will be selected at random
 21 by the “selecting a particle without looking” method. All attempts will be made to test
 22 undisturbed water-worked particles. Additionally, roughly 20 particles of each size class
 23 (32 mm, 45 mm, 64 mm, 90 mm, 128 mm) will be gaged to determine a representative
 24 distribution of forces for each class for each area that typifies a channel feature (e.g.,

1 thalweg, bar head, bar chute, bar toe) that traverses the cross sections. All gaged particles
2 will be measured for mass, 3D axes, and qualitatively described for rounding. Each
3 particle's gaged force, mass, and size will be used to predict the friction angles with
4 respect to the median particle size determined from a local pebble count and/or bed
5 photographs.

6 **28.4.2 Bed Photographs**

7 Photographs of the bed will be taken to produce a high-resolution grain size analysis that
8 includes the superficial sand-sized portion of the bed's surface. Additionally, from these
9 photos we will determine the degree of packing on the bed surface, which may assist with
10 calculating the critical shear stress for incipient motion of a particle. The photographs
11 will be taken through a scope with a plexiglass bottom. The scope will straddle a
12 measuring tape stretched between the two monuments that delineate the cross section so
13 as to note the distance from the left bank's monument. Attempts will be made to
14 photograph as much of the bed along the monitoring cross sections as possible, with the
15 main constraints being flow depth and velocity.

16 **28.4.3 Pebble Counts**

17 Pebble counts will be performed along the monitoring cross sections, not to exceed 30
18 feet distance from the cross section. A pebble count will be performed at intervals of
19 approximately every 10 to 20 feet of width parallel to the cross sections. Width will
20 depend on the variance exhibited in the cross-sectional profile and surface texture. This
21 level of resolution should provide adequate information on trends in grain size with
22 location along the cross section. Grain size statistics will be calculated from the pebble
23 count results. The statistics will be used in calculating the critical shear stress for particle
24 mobility as well as for calibrating the roughness in the flow model.

25 **28.4.4 Topographic Surveys**

26 Conventional and Real Time Kinematic (RTK) GPS survey equipment will be used to
27 survey the channel bathymetry. The channel bathymetry will be used to create the
28 topographic mesh boundary condition within the flow model). Included in these surveys
29 will be water's edge, edge of banks, and staked cross sections intended for repeated
30 survey so as to observe changes in channel geometry with time. Water's edge
31 measurements will be used to calibrate the flow model. The repeated cross-sectional
32 topographic surveys will also be used as a means of validating the sediment transport
33 model and channel evolution predictions.

34 **28.4.5 Flow Profile Surveys**

35 An acoustic Doppler current profiler (ADCP) fitted with either a differential GPS (1
36 meter horizontal accuracy) or RTK GPS (2 cm horizontal accuracy) will be used to
37 measure channel flow hydraulics for elevated flows in the vicinity of the tracer cross
38 sections and study sites. Results from the survey will be used to compare flow attributes
39 in the vicinity of the tracers with their movement or lack thereof. Also, the ADCP
40 velocity results will be used to calibrate the flow model.

1 **28.4.6 Scour Chain Monitoring**

2 Scour chains will be installed in the vicinity of the tracer cross sections and surveyed to 2
3 cm of horizontal accuracy to assist in future location. They will be placed at distances
4 suited to cover the range in lateral topographic variation and will likely be on the order of
5 every 20 feet across the channel width. Similar to the repeat topographic surveys, the
6 results from the scour chains will be used as a means of validating the sediment transport
7 and channel evolution model's predictions.

8 **28.4.7 Gravel and Cobble Tracers**

9 Particles greater than 32 mm in intermediate diameter will be collected from areas where
10 they will later be placed as tracers. These particles will be transported back to the
11 laboratory for measurement of size, mass, and roundness, and inserted with inductively
12 charged RFID tag. The RFID tag's unique identification code will be recorded with its
13 measurements. Additionally, the tracer will be painted for ease of locating, especially
14 when buried so as to record the burial depth. Placement of the tracers will be along the
15 monitoring cross sections spanning the channel's width. Each tracer will be positioned on
16 the bed such that it replaces a similar particle's size, shape, and relative position to
17 surrounding particles. Tracers will be placed before high-flow events, and their initial
18 locations will be surveyed using RTK GPS equipment. The surveyed latitude, longitude,
19 and elevation will be recorded with other measurements and RFID code. During high
20 flows, hydraulic properties proximal to the tracer lines will be surveyed using an ADCP
21 with the primary intention of recording near-bed velocities as well as for calibrating a 2D
22 flow model. After flows return to safe levels for accessing the channel, the tracers will be
23 relocated and their new position surveyed as before. The extent of bed material
24 mobilization will then be compared to discharge levels as recorded from local pressure
25 transducers maintained by DWR. The results of the tracer movements and the calibrated
26 flow model will be used to test the computed critical shear stress. Finally, by mapping
27 grain size distribution using the pebble count and bed photography results it will be able
28 to calculate the area and degree (i.e., nonmobile, partial mobility, fully mobile) of the bed
29 mobilized for differing flow scenarios.

30 **28.4.8 Flow and Sediment Transport Model**

31 A flow and sediment transport model will be used to predict flows capable of producing
32 mobilization of the reinforced bed material. These rare, elevated flows will expand the
33 area of usable spawning gravels and therefore provide a management alternative to
34 enhancing the bed surface for restoration purposes. A computational grid was developed
35 using the USGS's Multi Dimensional Surface Water Modeling System (MD_SWMS) and
36 computed hydraulic conditions using FaSTMECH's 2-D flow software (Nelson and
37 Smith, 1989). The FaSTMECH model will be used as a predictive tool for (1) calculating
38 local hydraulic parameters (i.e., shear stress and velocity) as they vary laterally and
39 longitudinally in the channel, and (2) predicting the conditions experienced under rare,
40 high-magnitude discharge events. Drag coefficients are the variable of adjustment to
41 calibrate the model. Surveyed roughness elements (i.e., bed forms, vegetation patches)
42 and measured bed texture will be used as the basis for specifying the channel roughness.
43 Additional tuning of the model will be performed using the ADCP-measured velocity
44 vectors to adjust local roughness elements (e.g. LWD and vegetation). Tracer gravels will
45 be used to determine locations that incurred mobility under differing flow levels and

1 determine the critical shear stress for grain entrainment. Assigning the calculated critical
2 shear stress into the sediment transport component of the model the transport rate will be
3 calculated. Additional validation of the model results will include the scour chain and
4 repeat topographic surveys as they will confirm FaSTMECH's channel evolution
5 component.

6 **28.5 Schedule**

7 These field tasks have been commenced at two riffle clusters (Riffle Cluster 38 and 40,
8 MEI, 2008) located at RM 260.7 and RM 261.6 in January 2010 and July 2010,
9 respectively. Six cross sections at each site have been staked across the channel width for
10 future comparison. Each has had repeated topographic surveys, ADCP measurements of
11 cross-sectional hydraulic measures, tracers deployed, force gage surveys, pebble counts,
12 and bed photo-surveys.

13 With the recent high-flow levels (approximately 7,800 cfs) we expect to be able to
14 quantify the maximum bed area maintained under the Restoration flow levels at the
15 monitored sites. Ideally, the tracers would be used in flow conditions that are close to the
16 conditions needed for incipient motion so as to better estimate the critical shear stress
17 component of the transport function. Therefore, we will attempt to survey the locations of
18 all tracers that have been deployed and replace those that have been mobilized with the
19 intention of verifying the critical shear stress calculated from direct field measurements.

20 Each of the field measurements listed in the methods section may be repeated and/or
21 extended to additional sites. Reasons for repeating these measurements would include (1)
22 changes in bed texture from scour and or deposition, (2) changes to channel geometry, (3)
23 to acquire additional information (e.g., data points for mobilizing flows), and/or (4) bed
24 armor disruption that causes a suspected change in the resistance of the bed's surface
25 material. Additional sites may be added to the study to (1) expand our understanding of
26 mobility under conditions that are not bracketed by the two sites; (2) to test the model's
27 predictions; or (3) to monitor gravel augmentation or restored sites. It is the intention of
28 this study to be able to expand the model's predictive capability throughout Reach 1A, or
29 at least to those areas expected to have flow conditions suitable for channel and habitat
30 maintenance and successful spawning and incubation.

31 **28.6 Deliverables**

32 The results of each component in the methods, including force gaging, bed material
33 characterization, pilot tracer study, and flow hydraulic survey methods, and preliminary
34 results are presented in the February 2010 ATR. Results from the tracer studies,
35 topographic surveys, hydraulic surveys, and force gage measurements are presented in
36 the February 2011 ATR. A report detailing investigation activities, analysis, results, and
37 conclusions will be presented as an appendix of the 2013 ATR. Similarly, additional data
38 collected as a part of this investigation will be presented as an attachment of the 2013
39 ATR.

1 **28.7 Point of Contact/Agency**

2 Matthew A. Meyers, P.G./DWR
3 (559) 230-3329
4 mmeyers@water.ca.gov

5 **28.8 References**

- 6 California Department of Water Resources (DWR). 2009. Fall 2009 Interim Flows
7 Monitoring Data Report for the San Joaquin River Restoration Program, Draft.
8 March 26.
- 9 DWR. *See* California Department of Water Resources. Jones & Stokes Associates and
10 Mussetter Engineering, Inc. (JSA and MEI). 2002. Development of San Joaquin
11 River Restoration Plan for Friant Water Users Authority and Natural Resources
12 Defense Council. January.
- 13 Kondolf, G.M. 2000. Assessing salmonid spawning gravel quality. *Trans. Amer. Fish.*
14 *Soc.* 129:262-281.
- 15 McBain and Trush, Inc. (eds). 2002. San Joaquin River Restoration Study Background
16 Report. Prepared for Friant Water Users Authority, Lindsay, California, and
17 Natural Resources Defense Council, San Francisco, California.
- 18 MWI. *See* Mussetter Engineering, Inc.
- 19 Moir, H.J., C.N. Gibbins, J.M. Buffington, J.H. Webb, C. Soulsby, and M.J. Brewer.
20 2009. A new method to identify the fluvial regimes used by spawning salmonids.
21 *Can. J. Fish. Aquat. Sci.* 66: 1404-1408.
- 22 Mussetter Engineering, Inc. (MEI). 2002. Hydraulic and Sediment-Continuity Modeling
23 of the San Joaquin River from Friant Dam to Mendota Dam, California. Prepared
24 for the U.S. Department of the Interior, Bureau of Reclamation, Fresno,
25 California. Contract No. 98-CP-20-20060. August.
- 26 ———. 2008. Draft San Joaquin River Data Collection and Monitoring Plan. Prepared
27 for the Department of Water Resources, Fresno, California, Task Order No. 6,
28 August 27, 2008. Stillwater Sciences, 2003. Draft Restoration Strategies for the
29 San Joaquin River. Prepared for Friant Water Users Authority and Natural
30 Resources Defense Council, California. February.
- 31 Nelson, J.M., and J.D. Smith. 1989, Flow in meandering channels with natural
32 topography, in Inkeda, S., and Parker, G., eds., *River meandering*: Washington,
33 D.C., American Geophysical Union Water Resources Monograph v. 12, p. 69-
34 102.

- 1 Reisser, D.W., M.P. Ramey, and T.A. Wesche. 1989. Flushing flows, in Alternatives in
2 Regulated River Management. Eds. J. A. Gore and G. E. Petts. Ch. 4, pp. 91-135.
3 CRC Press, Boca Raton. Florida.
- 4 San Joaquin River Restoration Program (SJRRP). 2009. Fisheries Management Plan: a
5 Framework for Adaptive Management in the San Joaquin River Restoration
6 Program. 147 pages plus appendices. June 2009.
- 7 SJRRP. *See* San Joaquin River Restoration Program.
- 8 Stillwater Sciences. 2003. Draft Restoration Strategies for the San Joaquin River.
9 Prepared for Friant Water Users Authority and Natural Resources Defense
10 Council. California. February.
- 11 Wilcock, P.R., G.M. Kondolf, W.V.G. Matthews, and A.F. Barta. 1996. Specification of
12 sediment maintenance flows for a large gravel-bedded river. *Water Resources*
13 *Research*, 32(9): 2911-2921.