



San Joaquin River Restoration Program Mendota Pool Bypass and Reach 2B Improvements Project

Hydraulic and Sediment Transport Modeling Workshop

February 12, 2015 1:30 pm – 4:30 pm

SJRECWA Office



Agenda

1. Introductions
2. Mendota Pool Bypass and Reach 2B Project Overview
3. Conceptual Hydraulic Design
4. Sediment Transport Modeling
 1. Degradation / Aggradation
 2. Water Surface Elevation Changes
5. Floodplain Inundation Analysis
6. Input
7. Next Steps

Katrina Harrison


MENDOTA POOL BYPASS AND REACH 2B PROJECT UPDATES

Reach 2B EIS/R Status

- Working on administrative drafts of EIS/R
- Public Draft EIS/R Anticipated for May 2015 release
- Will contain a preferred alternative


Reach 2B Project Update

EIS/R Process and Schedule



Reach 2B Project Update

Project Process and Schedule



Reach 2B Project Alternatives

- Four Alternatives presented in the Reach 2B Project Description TM
 - Compact Bypass with Narrow Floodplain and South Canal
 - Compact Bypass with Wide Floodplain and Bifurcation Structure (will be modified to become Preferred Alternative)
 - Fresno Slough Dam with Narrow Floodplain and Short Canal
 - Fresno Slough Dam with Wide Floodplain and North Canal



Reach 2B Preferred Alternative

- Based on landowner consensus based alternative
- Updated based on discussions with landowners and more information about infrastructure
- Tentatively Preferred Alternative:
 - Compact Bypass
 - Modified levee alignment – between narrow and wide
 - Bifurcation Structures for delivery to Mendota Pool



Reach 2B Preferred Alternative

- Fresno Slough Dam
 - Reduces Mendota Pool Volume
 - Changes to Operation
 - Mendota Dam recently repaired
- Compact Bypass
 - Landowner Consensus-Based Alternative
 - Larger floodplain
 - Same Delta Mendota Canal / Mendota Pool operations
- Public comment to date indicates Compact Bypass is Preferred



Reach 2B Preferred Alternative


- **Narrow Levee Alignment**
 - Minimizes land out of production
 - Landowner Consensus-Based Alternative
- **Wide Levee Alignment**
 - Maximizes fish habitat
- **Some landowners willing to sell land outside of Narrow Levee Alignment**
- **Preferred Levee Alignment is Narrow, with areas landowners are willing to sell**
- **Slightly (~20 acres) smaller than Wide Levee Alignment**



Reach 2B Preferred Alternative

- South or North Canal Options
 - Create access issues to farms – would require bridges
 - Take land out of production away from the river
 - Could move river side of the Chowchilla Bifurcation Structure downstream
 - Minimizes fish obstacles
 - Impacts flood operations
- Bifurcation Structures
 - Minimize land out of production
- Public comment to date indicates Bifurcation Structures are preferred

Reach 2B Preferred Alternative



Reach 2B Construction Schedule

- Must sequence project due to funding stream
- Preliminary schedule, based on Framework for Implementation:
 - Compact Bypass and structures to be constructed first
 - 2017 start
 - Reach 2B Levees second
 - 2020 start
- Design currently ongoing for Compact Bypass

Reach 2B Design Process

- Now: Compact Bypass Hydraulic Design
- March – Summer 2015: Levee and Structure Design for the Compact Bypass
- Fall 2015: Start work on 60% design
- No detailed designs and plans completed yet.

Reach 2B Design Public Input

- Technical Workshops at key decision points in the design process
- Summer 2015 Workshop anticipated on structure design

Blair Greimann

COMPACT BYPASS HYDRAULIC DESIGN

RECLAMATION

Managing Water in the West


Compact Bypass Grading Options

Blair Greimann
Hydraulic Engineer
Sedimentation and River Hydraulic Group
Technical Service Center, Denver, CO
bgreimann@usbr.gov



U.S. Department of the Interior
Bureau of Reclamation

SAN JOAQUIN RIVER
RESTORATION PROGRAM



Background

- **Hydraulic and Revegetation Design previously done at Appraisal Level**
- **Now we are progressing to the early design phases.**
- **Designing for the Compact Bypass first as it will be constructed first. The first major design decision in the Compact Bypass is the elevation of the flow control structure at its upstream end.**
- **There will be more opportunities for future input and review**
- **Looking to choose the elevation of the structure in the next month**

Outline

- **Conceptual Hydraulic Designs**
 - Grade Control Options
- **Sediment Transport Modeling Results**
 - Bed Changes
 - Water Surface Elevation Changes
- **Floodplain Inundation Analysis**
 - Wetted Width Changes
 - Tradeoffs

CONCEPTUAL DESIGNS

RECLAMATION


Design Criteria

- 1. Pass all life stages of Chinook salmon, pass sturgeon and pass other native species upstream and downstream through the Mendota Bypass project area.**
- 2. Promote survival of the species through development of appropriate and sustainable habitat.**
- 3. Create a bypass channel around Mendota Pool to ensure conveyance of at least 4,500 cfs through Reach 2B to Reach 3. This improvement requires construction of a structure capable of directing flow down the bypass and allowing the Secretary to make deliveries of San Joaquin River water into Mendota Pool when necessary.**
- 4. Maintain current flood conveyance capacities in Reach 3.**
- 5. Minimize both construction and maintenance cost.**
- 6. Create a sustainable stream profile that minimizes long term sediment imbalances within the project area**


Design Options for Grading

- **Option 1: Grade Control Profile**
 - Stabilization of the Compact Bypass with 6 one-foot grade control structures
- **Option 2: Natural Stream Profile**
 - Two one-foot channel stabilization features
 - Allows for more erosion in Reach 2B and deposition in Reach 3
- **Both options include a gated flow control structure at upper end of Compact Bypass to divert flows from San Joaquin into Mendota Pool**

Design Option Profiles



Design Option Profiles




Option 1



Example Riffle Section at Upstream end of each Rock Ramp

Compact Bypass Option 1
RS = 2500




Legend

- WS 4500 cfs
- WS 2000 cfs
- WS 1200 cfs
- WS 200 cfs
- WS 100 cfs
- Ground
- Levee
- Bank Sta


Example Pool Section between Rock Ramps

Compact Bypass Option 1

RS = 2200



Option 1: Rock Vanes for Bank Protection




Preliminary Draft, Subject to Change

EWP Stream Barb Design Sheet	
Date: _____ Site Location: _____ Species: _____	Project: _____ Design: _____ Date: _____


Option1: Rock Ramps for Grade Control - example




Option 1: Initial Water Surface Profile




Option 1: Initial Channel Velocities




Option 2




Option 2: Typical Cross Section



Option 2: Initial Water Surface Profile



Option 2: Initial Channel Velocities





SEDIMENT TRANSPORT MODELING RESULTS


RECLAMATION

Sediment Transport Modeling


- SRH-1D
- Cross section based simulation
- 50-year simulation
- Reach 2A through Reach 3
- Used simulated flows under SJRRP conditions




**SJB Suspended Sediment Concentrations
(WY 2010 - 2012)**




SJB Bed Load, WY2010 through WY2012




Future Bed Elevations Changes: Opt 1




Future Bed Elevations Changes: Opt 2



Future Bed Elevation Changes



Changes to Water Surface Elevation in Reach 3



Simulations do not indicate that 4500 cfs will encroach into the 3 feet of freeboard

Preliminary Draft, Subject to Change

RECLAMATION

Sediment Transport Modeling Results

- Some deposition 0.7 to 1 mile downstream from Compact Bypass / Reach 3 intersection
- Reach 3 is eroding in the long-term due to increase in flows under SJRRP
- 0.23 foot increase in water surface elevation from Scenario 1
- 0.25 foot increase in water surface elevation from Scenario 2
- Still 3 feet of freeboard

Sediment Transport Modeling Results

- **Maximum WSEL Change of 3 inches**
- **3 foot of freeboard maintained on all levees**
- **Entire area of deposition is added to EIS/R**
- **Possible levee improvements to increase height by a few inches included in EIS/R**
- **May or may not need levee improvements with more refined design**


FLOODPLAIN INUNDATION CHANGES

RECLAMATION


Hydraulic Modeling

- **1D Hydraulic Modeling**
- **Top Width as correlary for floodplain area**
- **Erosion 3.5 miles to 4 miles upstream in Reach 2B**
- **Lower portion of Reach 2B is currently Mendota Pool**
- **Returning the average river gradient will decrease inundation**


Changes to Inundation in Reach 2B



Changes to Inundation in Reach 2B



Changes to Inundation in Reach 2B



Potential methods to increase floodplain habitat

- Increase floodplain excavation and contouring to create high flow channels and lower floodplain surfaces.
- Increase roughness in Compact Bypass and Reach 2B to increase water surface elevations.
- Operating or design of the gates at the upstream end of the Bypass to increase water surface elevations in Reach 2B.
- Increase in the quality of floodplain habitat

Floodplain Inundation

- 144 acres of suitable habitat needed in Reach 2B based on Minimum Floodplain Habitat Area Report (December 2012)
- Will do 2D hydraulic modeling of proposed option and verify we still meet required suitable habitat

Comparison between Options 1 and 2

- **Option 1**
 - **More certainty in channel geometry**
 - **Less erosion of bed in Reach 2B**
 - **Additional maintenance of grade control structures will be necessary**
 - **Higher channel velocities in Compact Bypass**
 - **More bank erosion, and more bank protection necessary**
 - **More difficult upstream fish passage**

Comparison between Options 1 and 2

- **Option 2**
 - **Reduced construction and maintenance cost of grade control structures**
 - **Lower channel velocities**
 - **Less bank erosion, reduced need for bank protection**
 - **Better upstream fish passage**
 - **Additional erosion of channel in Reach 2B lowering water surface elevations and reducing floodplain inundation**
 - **Will likely still require one or two small grade control structures within Compact Bypass**
 - **Uncertainty in channel transition period after initial excavation**

All

INPUT FROM ATTENDEES

Questions?





Thank You

Katrina Harrison
Reach 2B Project Manager
916-978-5465
kharrison@usbr.gov

www.restoresjr.net